# Cable Connector 4-way, X-type with quick connector, IP68 3x4mm², 400V/25A

Marka: **Orno** | Symbol: **OR-AE-13623** | Ean: **5908254846489**




## PRODUCT DESCRIPTION

The 4-way cable connector X-type with a quick connector 400V/16A is a high-quality connecting element intended for applications requiring reliability and durability. High ingress protection rate of IP68 confirms possibility of outdoor installation, even in the ground, where high tightness as well as protection against water and dust are required.

The material from which the product is made boosts the safety of use in harsh environmental conditions. The

ORNO GROUP Sp. z o. o. All rights reserved.

connector is made of nickel-plated brass for guaranteed excellent conductivity and corrosion resistance. The insulation made from plastic and the housing made from polyamide (PA6) are known of high resistance to UV radiation. What is more, they are flame retardant (V1 flammability class).

The construction of the connector enables safe and stable connection of cables measuring 6 - 12mm in diameter. The cables are solidly and reliably joined with the help of a quick connector. The connector is 3-core which means that one may join up to 3 cores measuring max. 4 mm2 in cross-section. The product is best suited for two wires type H05VV-F 3x4mm$^2$ and H07RN-F 3x2,5mm$^2$.

The connector is intended for operation in wide range of temperatures (-40°C up to 105°C). The compact dimensions measuring 112x112 mm and Ø24 mm facilitate installation even within small spaces.

Our offer includes also straight MINI, standard as well as T- and X-type connectors and also corresponding models with screw connectors.

## TECHNICAL DATA

### General information:

| | |
|---|---|
| **Connector type:** | typu X |
| **Rated voltage [V]:** | 400 |
| **Current [A]:** | 16 |
| **Contact material:** | Mosiądz niklowany |
| **Insulating material:** | Tworzywo sztuczne |
| **Number of conductors:** | 3 |
| **With protective conductor:** | Tak |
| **Nominal cross section conductor [mm2]:** | 4 |
| **Nominal wire diameter [mm]:** | 6-12 |
| **Recommended cable:** | H05VV-F 3x4mm2 / H07RN-F 3x2,5mm2 |
| **Type of connection:** | Szybkozłączka |
| **Underground installation::** | Tak |
| **Suitable for:** | H07RN-F |
| **Housing material:** | PA6 |
| **Flame retardant housing:** | Tak |

ORNO GROUP Sp. z o. o. All rights reserved.

| | |
|---|---|
| **Body fire rating UL94:** | V1 |
| **UV-resistance:** | Tak |
| **Degree of protection (IP):** | IP68 |
| **Working temperature:** | (-40 - +105) |
| **Width [mm]:** | 112 |
| **Height [mm]:** | 112 |
| **Diameter [mm]:** | 24 |
| **Weight [g]:** | 74 |







ORNO GROUP Sp. z o. o. All rights reserved.



ORNO GROUP Sp. z o. o. All rights reserved.