PORTO S LED 10W floodlight with PIR motion sensor, 800lm, IP44, 4000K, aluminium + polycarbonate

Marka: **ADVITI** | Symbol: **AD-NL-6462BLR4** | Ean: **5908254840456**



PRODUCT DESCRIPTION

The PORTO S LED frameless floodlight with motion sensor is a 10W product with a luminous flux of 800lm. As a result, it provides a strong and clear light that is ideal for use in many locations, including outdoors.

The device is made from shatterproof aluminium and a plastic diffuser. The upgraded IP44 protection level means that the floodlight is protected against dust and water, making it ideal for outdoor use.

ORNO GROUP Sp. z o. o. All rights reserved.

The floodlight has a functional PIR motion sensor, which activates the light when movement is detected. In this way, it prevents unnecessary energy consumption and enables us to illuminate the chosen space when it is actually needed, providing comfort and savings.

PORTO S LED emits pleasant light with a neutral white colour of 4000K, allowing for comfortable functioning and working. LEDs as a light source allow for low electricity consumption, which has a positive impact on the wallet of users and the environment.

TECHNICAL DATA

General Information:

Nominal voltage [V]:	230
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	10
Luminous flux [lm]:	800
With light source:	tak
Colour temperature [K]:	4000
Beam angle:	Wiązka bardzo szeroka > 80°
Rated life time L70/B50 at 25 °C [h]:	35000
Colour rendering index CRI:	80-89
Power factor:	>0,9
Energy efficiency class of the built-in lamp:	F
Colour of light:	Neutralny biały
Flickering value Pst LM:	<1
Degree of protection (IP):	IP44
Impact strength:	IK08
Protection class:	I
Suitable for surface mounting:	tak
Suitable for wall mounting:	tak
Tripod mounting:	tak
Material housing:	Aluminium

ORNO GROUP Sp. z o. o. All rights reserved.

Material cover:	Tworzywo sztuczne matowe/satynowe
Covering of the luminaire with thermally insulating material possible:	nie
Colour housing:	Czarny
With movement sensor:	tak
With light sensor:	tak
Sensor type:	PIR
Detection range:	0,5-8m ± 2m
Adjustable daylight sensor :	tak
LUX light adjustment range:	5-2000lux
Adjustable time setting :	tak
TIME adjustment range:	5s ± 3s - 10min ± 3min
Adjustable detection range:	tak
Width [mm]:	127
Height/depth [mm]:	48
Length [mm]:	109
Exchangeable control gear:	nie

ORNO GROUP Sp. z o. o. All rights reserved.









ORNO GROUP Sp. z o. o. All rights reserved.



ORNO GROUP Sp. z o. o. All rights reserved.