GEMINIX LED 2x10W, work floodlight, portable with rechargeable battery, 1200lm, IP44, 4000K, 5000mAh

Marka: **ADVITI** | Symbol: **AD-NR-6466L4** | Ean: **5908254840760**



PRODUCT DESCRIPTION

A work floodlight for illuminating workplaces and areas where there is no access to a permanent light source. It is a rechargeable lamp that can be used both indoors and outdoors. The 5000 mAh battery provides a long operating time of up to five hours. A charging cable is also included for easy recharging of the battery. The LEDs emit a luminous flux of 1200lm (2x600lm).

Equipped with two independently movable and independently illuminating heads, the floodlight offers the

ORNO GROUP Sp. z o. o. All rights reserved.

possibility to precisely direct the light so that two work zones can be illuminated at the same time. In addition, this lamp has a folding tripod, making it easy to carry and set up in different conditions.

One of the most interesting features of this floodlight is that it can be used as a powerbank. This means that, if necessary, it can be used to charge mobile devices such as a phone or tablet. This feature makes the floodlight particularly useful in situations where you are short of a power source, for example on a camping trip.

The lamp is also waterproof (IP44), which means it will be great for outdoor use. The battery charge indicator informs the user of the battery's charging status, which is particularly useful if you plan to take the lamp to a location where you will not have access to a power source.

The floodlight is a very practical tool for both professionals and private individuals carrying out various types of work. Its mobility and functionality make it the right choice for many users who want versatile and long-lasting use.

TECHNICAL DATA

General information:

Nominal voltage [V]:	5
Lamp type:	LED, niewymienne
Battery capacity [mAh]:	5000
Type of battery:	Akumulator Li-po
Battery included:	tak
Suitable for lamp power [W]:	20
Rated luminous flux according to IEC 62722-2-1 [lm]:	1200
Suitable for number of lamps:	2
With light source:	tak
Colour temperature [K]:	4000
Rated life time L70/B50 at 25 °C [h]:	50000
Colour rendering index CRI:	80-89
Colour of light:	Neutralny biały
Degree of protection (IP):	IP44
Impact strength (IK):	IK08

ORNO GROUP Sp. z o. o. All rights reserved.

Material housing:	Nylon/Guma
Colour housing:	Czarny/Żółty
Voltage type:	DC
With switch:	tak
Width [mm]:	200
Height/depth [mm]:	135
Length [mm]:	60
Other features:	Wejścia ładowania USB-C, czas pracy przy pełnym naładowaniu 5h, funkcja powerbank, wskaźnik naładowania baterii





ORNO GROUP Sp. z o. o. All rights reserved.









ORNO GROUP Sp. z o. o. All rights reserved.



ORNO GROUP Sp. z o. o. All rights reserved.