SOLIS LED 10W, solar floodlight with PIR sensor, 1200lm, IP54, 4000K, 3000 mAh, black

Marka: **ADVITI** | Symbol: **AD-SL-6467BLR4** | Ean: **5908254840777**



PRODUCT DESCRIPTION

The SOLIS LED solar wall floodlight with motion sensor and 3000mAh battery perfectly works as alternative to traditional lighting. This innovative, ecological and economical solution provides a safe illumination of a driveway, a car park or your property. In the first place, it ensures less energy consumption.

All elements of the floodlight are mobile thus you may adjust the floodlight, solar panel or motion sensor according to your own needs.

ORNO GROUP Sp. z o. o. All rights reserved.

It is possible to install the solar panel together with the device or it may be installed in a distance of 2m from the floodlight in more sunny location.

The light emitted by the device has pleasant and neutral color (4000K). The high degree of ingress protection IP54 ensures protection against dust, dirt and contact with water, and guarantees resistance to all weather conditions.

The SOLIS LED floodlight has a built-in PIR motion sensor that switches on the light exactly when we need it. Additionally, thanks to a twilight sensor it is possible to program the floodlight so that it switches on automatically after dark. Maximum detection range is 8m.

The installation of the floodlight is easy and simple, and the device itself does not require any calibration and is ready for use immediately after connection.

TECHNICAL DATA

General information:

Battery capacity [mAh]:	3000
Type of battery:	3,7V Li-ion
Battery included:	tak
Suitable for lamp power [W]:	10
Luminous flux [lm]:	1200
With light source:	tak
Colour temperature [K]:	4000
Rated life time L70/B50 at 25 °C [h]:	25000
Colour rendering index CRI:	80-89
Colour of light:	Neutralny biały
Degree of protection (IP):	IP54
Impact strength:	IK06
Protection class:	III
Suitable for surface mounting:	tak
Suitable for wall mounting:	tak
Material housing:	Tworzywo sztuczne

ORNO GROUP Sp. z o. o. All rights reserved.

Material cover:	Tworzywo sztuczne matowe/satynowe
Colour housing:	Czarny
With movement sensor:	tak
With light sensor:	tak
Sensor type:	PIR
Detection range:	8m
Adjustable daylight sensor :	tak
LUX light adjustment range:	15-1000lx
Adjustable time setting :	tak
TIME adjustment range:	10-60s
Adjustable detection range:	nie
Solar panel:	tak
Type of solar panel:	CdTe cienkowarstwowy
Width [mm]:	178
Height/depth [mm]:	290
Length [mm]:	140
Other features:	Kabel 2 m

ORNO GROUP Sp. z o. o. All rights reserved.









ORNO GROUP Sp. z o. o. All rights reserved.









ORNO GROUP Sp. z o. o. All rights reserved.