

TECHNICAL CARD



LED Headlamp

INDEX: VLF-H047Z



WARRANTY 2 YEARS

General parameters

Operation mode	TURBO, HIGH, MIDDLE, LOW, RED HIGH, RED MIDDLE, RED LOW, RED FLASH
Light source replaceable	no

Type of light source

Dimmable	yes
Technology	LED

Electrical parameters

Input interface	USB-C
-----------------	-------

Photometric parameters

Useful luminous flux of the contained light source (Φ_{use})	1000 Lm
Peak luminous intensity	11660 cd
Correlated color temperature	5000K (neutral white), Red

Additional information

Fall protection	1 m
-----------------	-----

Housing colour	Black
Battery voltage	3.7 V
Battery capacity	2000 mAh
Battery type	Li-pol
Battery indicator	5 level
Battery replaceable	no
Operating temperature range	-20° +40°C
Mercury content	Does not contain
Ingress protection	IP65
Housing material	Polyamide

Dimensions

EAN	4820246489560
Height	49 mm
Width	80 mm
Depth	46 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	123g

Signs marking goods

Packaging marking	CE, Utilization
-------------------	-----------------

VIDEX[®]**VIDEX VLF-H047Z 1000Lm 5000K****INDEX: VLF-H047Z**

VIDEX[®]**VIDEX VLF-H047Z 1000Lm 5000K****INDEX: VLF-H047Z**

VIDEX[®]**VIDEX VLF-H047Z 1000Lm 5000K****INDEX: VLF-H047Z**

VIDEX®

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z



VIDEX[®]

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

VIDEX®

VIDEX VLF-H047Z 1000Lm 5000K

INDEX: VLF-H047Z

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



We reserve the right to make technical changes. The data contained in this material is



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— Operating temperatures range



— The product supports brightness adjustment



— The product does not contain mercury



— Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions