

TECHNICAL CARD



Recessed spotlight luminaire



IK07



-25° +50°C



Free



IP20

WARRANTY 2 YEARS

General parameters

Light source replaceable end user

Electrical parameters

Maximum power Max 30W

Rated voltage, frequency AC 220-240 V, 50/60 Hz

Input interface Terminal block

Electric shock protection class II

Additional information

Base GX53

Impact protection IK07

Place of installation Ceiling, Recessed

Place of application indoor

Housing colour White

Operating temperature range -25° +50°C

Mercury content Does not contain

Ingress protection IP20

Housing material Aluminum

VIDEX for GX53 lamp VL-SPF33S-W

INDEX: VL-SPF33S-W

Dimensions

EAN	4820246488334
Height	40 mm
Width	105 mm
Depth	105 mm
In the package	1 pc.
Outer box	40 pcs.
Unit nett weight	110g

Signs marking goods



Packaging marking CE, Utilization



INDEX: VL-SPF33S-W

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.



The product must be used indoors



Class of protection against electric shock II - provided not only by basic insulation but also by double or reinforced insulation



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The product withstands a medium impact (e.g., from a blunt object)



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. Protection against solid objects larger than 12 mm; no protection against moisture