

**INDEX: VLF-A376** 

## **TECHNICAL CARD**



LED Portable Flashlight





# SHOCK RESISTANT









#### **WARRANTY 3 YEARS**



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

#### **General parameters**

Operation mode	TURBO, HIGH, LOW, MOON, STROBE, RED HIGH, RED LOW, RED FLASH
Light source replaceable	no
Battery Warranty	1 year

#### Type of light source

Dimmable	no
Technology	LED

#### **Electrical parameters**

On-mode power (Pon)	20 W
Input interface	USB-C

#### **Photometric parameters**

#### VIDEX VLF-A376 3600Lm 5000K

**INDEX: VLF-A376** 

Useful luminous flux of the contained light source ( <b>Φ</b> use)	3600 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	21440 cd

#### **Additional information**

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 21700, Li-ion 18650
Battery voltage	3.7 V
Battery capacity	4000 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

#### **Dimensions**

EAN	4820246487177
Height	152 mm
Depth	29 mm
Width	40 mm
In the package	1 pc.
Outer box	20 pcs.



### VIDEX VLF-A376 3600Lm 5000K

**INDEX: VLF-A376** 

Unit nett weight

135g

#### **Signs marking goods**

Packaging marking

CE, Utilization











**INDEX: VLF-A376** 





We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



#### VIDEX VLF-A376 3600Lm 5000K

5/5

**INDEX: VLF-A376** 



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



 The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



The product does not contain mercury



Class of protection against dust and moisture. The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter

Date: 17.06.2025